

BELT FEEDERS BWF SERIES

The BWF Series belt feeders are used to feed every type of material even with very irregular grain size. A strong aluminum frame ensures its rigidity; the integrated twin load cell system and the calibrated feeder ensure accuracy of feeding to the maximum required standards.

Available in open release or totally enclosed for maximum protection and environmental cleanliness.



TECHNICAL CHARACTERISTICS

CHARACTERISTICS	STANDARD	ON REQUEST
Chassis material	Alluminium	Fe 360 – AISI 304
Feeder material	PVC	Food, wear resistant
Feeder centering system	Covex rollers	Pneumatic device
Feeder tensioning system	Manual	Counterweight
Feeder cleaning system	Wear resistant scrapers	PTFE Scrapers
Weight monitoring system	2 cell loading bridge	Version ATEX zone 2D
Speed monitoring system	Encoder	Version ATEX zone 2D
Optionals	See specific document	

BWF SERIES BELT FEEDERS

MODEL	dm ³ /h										
	0,1	5	10	15	20	25	30	35	40	50	80
BW025	Yellow	Yellow	Yellow								
BW035		Green	Green	Green	Green	Green					
BW055					Blue	Blue	Blue	Blue			
BW080							Orange	Orange	Orange		
BW120									Red	Red	Red